

LAWN AND LEAF COLLECTION PRODUCTS

Residential

TRACTOR VACUUM



Flex-Tube® PV (Medium Weight)

Coextruded Clear PVC hose with rigid black PVC helix

- Economical
- Ultra smooth interior, crush resistant
- OEM lengths and colors available
- Wall thickness .035"



SIZE	4", 5", 6", 7", 8", 10"
LENGTH	12', 25'
TEMP RANGE	20° to 160°

Flex-Tube® PU (Medium Weight)

Coextruded clear thermoplastic ether based polyurethane with rigid yellow ABS helix

- Great abrasion resistance
- Ultra smooth interior, crush resistant
- Puncture and tear resistant
- OEM lengths and colors available
- Wall thickness .035"



SIZE	4", 5", 6", 7", 8", 10"
LENGTH	12', 25'
TEMP RANGE	-40° to 200°

Flex-Tube® Bridge Clamps



Specially designed stainless steel band and welded stainless steel bridge with carbon steel screw

- Fits over helix creating a leak proof seal
- Available in sizes 4" to 10"

Commercial/Landscaping

TRUCK LOADERS



Flexadux® LCDC (Medium Weight)

High performance polypropylene blend hose reinforced with a spring steel wire helix and external polypropylene wearstrip

- Economical
- Light weight, drag resistant
- Long flex life with good abrasion and tear resistance
- Wall thickness .032"




SIZE	8", 10", 12"
LENGTH	10', 25'
TEMP RANGE	-30° to 200°

Flexadux® HT-W (Heavy Weight)

Thermoplastic rubber hose reinforced with a spring steel wire helix and external polypropylene wearstrip

- Great moisture and UV resistance
- External wearstrip offers additional drag resistance
- Puncture and tear resistant
- Wall thickness .045"



SIZE	8", 10", 12"
LENGTH	10', 25'
TEMP RANGE	-60° to 275°

Municipal Loaders

HEAVY-DUTY COMMERCIAL



Flx-Thane® HD (Heavy Weight)

Polyurethane hose reinforced with a coated spring steel wire helix

- Superior abrasion resistance & tear strength
- Ideal for leaf and debris collection
- Great moisture and UV resistance
- Excellent flexibility
- Also available in translucent blue
- Wall thickness .045"




SIZE	12", 14", 16", 18"
LENGTH	10', 25'
TEMP RANGE	-65° to 225°

Flx-Thane® VHD (Very Heavy Weight)

Polyurethane hose reinforced with a coated spring steel wire helix

- Great abrasion resistance & higher tear strength
- Severe service & debris collection
- Great moisture and UV resistance
- Wall thickness .060"



SIZE	12", 14", 16", 18"
LENGTH	10', 25'
TEMP RANGE	-65° to 225°

All Leaf Collection Hoses In Stock for the Season!