



INDUSTRIAL HOSE | EXTREMEFLEX BEVERAGE HOSE

EXTREMEFLEX™ BEVERAGE

Plicord® extremeFlex®
Beverage EZ Clean

EXTREME FLEXIBILITY.
EXTREME VERSATILITY.

GOODYEAR
ENGINEERED PRODUCTS

VEYANCE
TECHNOLOGIES

EXTREMEFLEX™ BEVERAGE

Enhanced flexibility for enhanced operational efficiencies

Ideal for beer, wine, distillery and beverage (edible liquid) transfer processing facilities, ExtremeFlex Beverage features a microbe-resistant Chlorobutyl tube that doesn't impart taste or smell. Suited for applications requiring flexible and/or tight bend connections, ExtremeFlex is lightweight, flexible and easy to handle.

- Rated for full suction
- High working pressure
- Better bend radius
- Phthalates free
- Corrugated EZ Clean cover for added abrasion resistance

Application: For beer, wine, distillery, and beverage (edible liquid) transfer processing facilities. Ideal for applications requiring flexible and/or tight bend connections.

Construction: TUBE: White Chlorobutyl (FDA/USDA compliant & conforms to 3-A Sanitary Standard 18-03) COVER: Corrugated grey chemical (wrapped impression), New Corrugated red EZ Clean UHMWPE cover (semi-smooth finish)
REINFORCEMENT: Spiral-plyed fabrics with double galvanized helix wire

Temperature: -30° F to 220° F (-34° C to 104° C)

Order Codes: 549-603 Gray Cover, 549-605 EZ Clean Red Cover

Couplings: Tri-Clamp or Sanitary ends are typically used with this hose

Take advantage of our complete line of food and beverage industry hose offerings:

- ExtremeFlex™ Food
- Vintner™
- Brewline®
- White Flexwing®
- Fortress® with Microban



EXTREMEFLEX™ BEVERAGE GRAY HOSE SPECIFICATIONS

Part Number	I.D.		O.D.		Working Pressure @ 72° F		Bend Radius		Vacuum @ 72° F		Weight	
	Inch	mm	Inches	mm	PSI	MPa	Inches	mm	Inches Hg	mm Hg	lb/ft	kg/m
20762678	1	25.4	1.56	39.7	250	1.72	1.5	38	29	737	.73	1.09
20762679	1.5	38.1	2.02	51.3	250	1.72	2.3	57	29	737	.92	1.38
20762751	2	50.8	2.53	64.2	250	1.72	3.0	76	29	737	1.20	1.79
20762752	3	76.2	3.59	91.2	200	1.38	4.5	114	29	737	2.02	3.01
20762753	4	101.6	4.60	116.8	150	1.03	6.0	152	29	737	2.76	4.11



EXTREMEFLEX BEVERAGE RED HOSE SPECIFICATIONS

Part Number	I.D.		O.D.		Working Pressure @ 72° F		Bend Radius		Vacuum @ 72° F		Weight	
	Inch	mm	Inches	mm	PSI	MPa	Inches	mm	Inches Hg	mm Hg	lb/ft	kg/m
20776605	1	25.4	1.52	38.7	250	1.72	2	51	29	737	.65	.96
20762754	1.5	38.1	2.03	51.6	250	1.72	3	76	29	737	.93	1.38
20752524	2	50.8	2.537	64.5	250	1.72	4	102	29	737	1.21	1.80
20762758	3	76.2	3.601	91.5	200	1.38	6	152	29	737	2.03	3.02
20762760	4	101.6	4.607	117	150	1.03	8	203	29	737	2.77	4.12



INDUSTRIAL HOSE | EXTREMEFLEX BEVERAGE HOSE

U . S . A .
1 - 8 0 0 - 2 3 5 - 4 6 3 2
F A X 1 - 8 0 0 - 7 6 2 - 4 0 1 7

C A N A D A
1 - 8 8 8 - 2 7 5 - 4 3 9 7
F A X 1 - 8 8 8 - 4 6 4 - 4 3 9 7

M E X I C O
0 1 - 8 0 0 - 4 3 9 - 7 3 7 3
F A X 0 1 - 8 0 0 - 0 6 2 - 0 9 1 8

GOODYEAR.EP.COM/HOSE

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company. Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates. ©2014 Veyance Technologies, Inc. All Rights Reserved.

700862906500

1098064 7/14

GOODYEAR
ENGINEERED PRODUCTS

VEYANCE
TECHNOLOGIES