

Novaflex®

Novabrew



Novabrew

NOVABREW is a state of the art designed hose based on the specific requirements of the today's modern breweries. NOVABREW has a rugged but flexible construction with a super-smooth white tube that is microbe resistant along with a dark burgundy cover that resists dirt scuffs and is easily cleaned. NOVABREW is built on stainless steel mandrels for cleanliness and Meets FDA, USDA and 3-A (certificate #1376) Standards.

Specifications

Tube: White Chlorobutyl

Reinforcement: Multiple plies of polyester tire cord dual monofilament

helix rods

Cover: Dark Burgundy EPDM

Temperature: -40° to 240°F (can be open end steam cleaned)

CIP to 248°F

Specification Chart

Part No.	ID"	OD"	WP psi	MBR	Vacuum	WT lbs/ft
6507NB-00750-00	3/4	1.26	250	4	Full	0.39
6507NB-01000-00	1	1.51	250	4	Full	0.48
6507NB-01500-00	11/2	2.02	250	5	Full	0.68
6507NB-02000-00	2	2.78	250	7	Full	1.27
6507NB-02500-00	21/2	3.28	250	13	Full	1.55
6507NB-03000-00	3	3.97	250	21	Full	1.89
6507NB-04000-00	4	4.78	250	40	20" HG	2.52

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex® hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex® hose and duct under conditions that duplicate the service conditions prior to installation.

02.2012

IN USA

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

New Jersey

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

IN CANADA

Ajax, Ontario 555 Beck Crescent Ajax, ON L17 1C9 tel (905)686-5200 fax (905) 686-8349

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com